


## 23100 Series



select	Anfrage Bezeichnung	Hauptabmessungen (mm)					Grundtragzahlen (KN)		Begrenzte Geschwindigkeit (U/min)		Gewicht (kg)
		D	D	B	RS min	Dynamisch (Cr)	Statisch (Cor)	Fett	Bohrinsel		
23120	100	165	52	2	310	470	1700	2600	4.3		
23120K	100	165	52	2	310	470	1700	2600	4.16		
23120KW33C3	100	165	52	2	310	470	1700	2600	4.16		
23120W33C3	100	165	52	2	310	470	1700	2600	4.3		
23122	110	180	56	2	370	580	1500	2400	5.4		
23122K	110	180	56	2	370	580	1500	2400	5.22		
23122KW33C3	110	180	56	2	370	580	1500	2400	5.22		
23122W33C3	110	180	56	2	370	580	1500	2400	5.4		
23124	120	200	62	2	455	705	1400	2100	7.7		
23124K	120	200	62	2	455	705	1400	2100	7.46		
23124KW33C3	120	200	62	2	455	705	1400	2100	7.46		
23124W33C3	120	200	62	2	455	705	1400	2100	7.7		
23126	130	210	64	2	495	795	1300	2000	8.47		
23126K	130	210	64	2	495	795	1300	2000	8.2		
23126KW33C3	130	210	64	2	495	795	1300	2000	8.2		
23126W33C3	130	210	64	2	495	795	1300	2000	8.47		
23128	140	225	68	2.1	540	895	1200	1800	10.2		
23128K	140	225	68	2.1	540	895	1200	1800	9.86		
23128KW33C3	140	225	68	2.1	540	895	1200	1800	9.86		
23128W33C3	140	225	68	2.1	540	895	1200	1800	10.2		
23130	150	250	80	2.1	730	1190	1100	1700	15.6		
23130K	150	250	80	2.1	730	1190	1100	1700	15.1		

## 23100 Series

23130KW33C3	150	250	80	2.1	730	1190	1100	1700	15.1
23130W33C3	150	250	80	2.1	730	1190	1100	1700	15.6
23132	160	270	86	2.1	840	1370	1000	1600	19.8
23132K	160	270	86	2.1	840	1370	1000	1600	19.2
23132KW33C3	160	270	86	2.1	840	1370	1000	1600	19.2
23132W33C3	160	270	86	2.1	840	1370	1000	1600	19.8
23134	170	280	88	2.1	885	1490	960	1500	21.5
23134K	170	280	88	2.1	885	1490	960	1500	20.8