


Four Row Series



select	Anfrage Lagernr.		Grenzabmessungen (mm)						Tragzahlen (kN)		Masse kg
			D	D	B	T	r min	r1 min	Dynamisch (Cr)	Statisch (Cor)	
77928	139.7	200.025	157.162	160.338	1.1	1.8	535	1870	16.2		
2077930	150	210	165	165	0.7	2.3	600	1590	21.2		
77730	150	225	136	136	3	2.5	540	1460	17.7		
2077134	170	260	230	230	3	2.5	940	3100	43		
77736	180	280	180	180	3	2.5	835	2540	39.6		
77740	200	310	200	200	3	2.5	1970	1520	55.6		
20777140	200	310	275	275	3	2.5	1230	4200	75.1		
77741	205	320	205	205	4	3	1060	2850	55.4		
20777144	220	340	305	305	4	3	2290	5950	99.5		
20777148	240	360	310	310	4	3	3300	210	90.5		
77750K	250	460	270	270	5	4	2250	6400	192		
382952/HC	260	360	265	265	3	2.5	1730	5050	77.8		
77752	260	400	255	255	3.7	7.5	1480	4950	117		
7752G	260	400	255	255	5	4	1910	490	117		
382052	260	400	345	345	5	4	2850	7700	161		
777752	260	440	300	300	2	5	2670	5850	182		
77756	280	420	250	250	5	5	1540	5300	119		
77860U	300	420	310	310	4	3	2020	8100	134		
2077160	300	460	390	390	5	4	3850	10200	222		
77760U	300	500	350	350	5	4	2730	8900	280		
2077164	320	480	380	380	5	4	3000	11500	252		
2077968	340	460	310	310	4	4	2200	9300	147		
371068	340	520	325	325	5	4	3200	8200	247		
77872	360	480	375	375	4	4	2550	11800	197		

Four Row Series

1077772	360	600	420	420	4.7	4.7	3950	13500	388
77776	380	550	330	350	5	5	2490	9450	273
3077776	380	620	388	388	6	6	3450	11600	443
381176/HC	380	620	420	420	5	4	5050	12600	485
381176/HCC9	380	620	420	420	5	4	5050	12600	485
77779	395	545	268.7	288.7	4	7.5	2130	6500	194